

# ON-LINE PC BUTTON DRIPPERS

# ClickTif HD



Heavy Duty Pressure-Compensating (PC) & Compensating Non-Leakage (CNL) online Button Dripper

# Taper lock outlet Barb outlet 3/5 PC CNL Barb outlet 3/5 CNL CNL

### **APPLICATIONS**

- Greenhouses, nurseries. orchards, Vineyards, landscapes and garden plots
- Pulse irrigation and irrigation in soilless conditions
- Prevents surplus drainage in low places (CNL model)

# **STRUCTURE AND FEATURES**

- Heavy Duty range of drippers and accessories in various configurations
- Four dripper design elements minimize clogging:
  - 1. Protected water inlet
  - 2. Flushing mechanism of regulating diaphragm
  - 3. Strong turbulent flow in labyrinth enables continual cleaning and flushing
  - 4. Large water passages
- Color-coded for identification of discharge and model
- Standard 5 mm tapered outlet for working with connectors or barb outlet for 3/5 tube
- Chemical-resistant, high-grade plastic for precision and durability
- Two models available: PC and CNL (Compensating Non-Leakage)
- Unique "sharp edge" CNL design prevents dirt accumulation and ensures reliable operation under difficult conditions
- 6 different flow rates

# COLOR CODE



# **TECHNICAL DATA**

- Nominal discharge: 1.3, 2.0, 3.0, 4.0, 8.0, 12.0 l/h
- Regulating pressure range: 0.5-4.0 bar
- Very low CV
- Minimum recommended working pressure 1.0 Bar
- Non-Leakage (CNL): Opening pressure: 8.0 m
  - Closing pressure: 3.0 m
- Filtration Recommendation: 130 micron (120 mesh)





# ClickTif **HD** Accessories



# **DROP GUIDE**

Use as single outlet for drop guide

# **LABYRINTH STAKES**

# Working with multiple outlets:

- 1. Use labyrinth stakes to improve uniformity
- 2. Minimum recommended working pressure: 1 bar
- 3. Maximum recommended flow per outlet: 2.0 l/h

# 2.5 mm Punch

Special design for comfortable punching and inserting of ClickTif drippers





2, 4, 8 outlets with flow control stakes

### 3/5 mmoutlet connectors



802908 802920

g no. Catalog no. 802940

## **Multi-level connectors**





Catalog no. 802928

Catalog no. 802948

